



FLOOR STANDING STORAGE TANKS WITH TWO HEAT EXCHANGERS

EV 7/5 S2 200 60

Capacity	197 L
Net weight	70 kg
Insulation	50 mm
Heat exchanger surface S1	0.75 m ²
Heat exchanger surface S2	0.54
Heat exchanger capacity S1	4.6 L
Heat exchanger capacity S2	3.3 L
Heat losses ΔT 45K	59 W
Energy class	B
Maximum operational temperature	95 °C
Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar



V40 - hot water delivered with a temperature of at least 40°C (S1)	304.4 L
V40 - hot water delivered with a temperature of at least 40°C (S2)	154.3 L
Diameter	600 mm
Minimum height of the premise	1345 mm



Information

EV 7/5 S2 200 60

- High-quality enamel coating ensuring long operating life
- Highly efficient PU insulation
- Efficient anode protection
- Service flange for easy inspection of the appliance
- Option for installation of an electric heating element
- Option for installation of a thermal regulator
- Option for installation of a thermal sensor

Serie information

EV 7/5 S2 200 60

The range includes models with volumes from 160 up to 2000 liters with two heat exchangers. Suitable to cover the demands of a single and multi-family residential buildings or industrial needs.