TESY
It's impressive



DOMESTIC HOT WATER TANKS CLASS B & C WITH TWO HEAT EXCHANGERS

EV 13/7 S2 1000 105 DN18 (EPS)

TIN Code	306393 (306820)
Range	932
Net weight	310 kg
Insulation	EPS 100 mm
Heat exchanger surface S1	3.45 m²
Heat exchanger surface S2	1.31 m²
Heat exchanger capacity S1	31.3 L
Heat exchanger capacity S2	7.9 L
Heat losses ΔT 45K	143 W

Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110 °C
Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar
V40 - hot water delivered with a temperature of at least 40□ (S1)	1403 L
V40 - hot water delivered with a temperature of at least 40□ (S2)	604 L
Diameter	1050 mm

Information

EV 13/7 S2 1000 105 DN18 (EPS)

- **TESY ThermoShell modular removable EPS INSULATION** for models 800 L and 1000 L
- High quality **ENAMEL COATING CrystalTech PRO**
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life:
  - **TWO MG+** anodes for models from 160 L to 1000 L
- **SERVICE OPENING** for easy inspection and maintenance.
- Option for **INSTALLATION** of different power rated **HEATING ELEMENTS**.
- Thermoregulator installation pocket.
- Pockets for thermo sensors.

Serie information

EV 13/7 S2 1000 105 DN18 (EPS)

The range includes models from 160 L to 2000 L with energy efficiency class B or C. Suitable for installation in single and multi-family residential buildings as well as for commercial application.

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.