TESY
It's impressive

DOMESTIC HOT WATER TANKS CLASS B & C WITHOUT HEAT EXCHANGERS WITH 2 INLETS AND 2 OUTLETS

EV 300 65 B

TIN Code	305600
Range	300
Net weight	68 kg
Insulation	PU 50 mm
Heat losses ΔT 45K	68 W
Energy class	B
Maximum operational temperature	95 °C
Rated pressure of the water tank	8 bar
Diameter	650 mm

Information

EV 300 65 B

- **CFC free PU foam INSULATION** for optimal heat losses for models up to 500 L.
- High quality **ENAMEL COATING CrystalTech PRO**
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life:
  - **TWO MG+** anodes for models from 160 L to 1000 L
- **SERVICE OPENING** for easy inspection and maintenance.
- Option for **INSTALLATION** of different power rated **HEATING ELEMENTS**.
- Thermoregulator installation pocket.
- Pockets for thermo sensors.

Serie information

EV 300 65 B

The range includes models from 200 L to 2000 L with energy efficiency class B or C. Suitable for installation in single and multi-family residential buildings as well as for commercial application.

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.