TESY
It's impressive



DOMESTIC HOT WATER TANKS CLASS B & C WITHOUT HEAT EXCHANGERS WITH 2 INLETS AND 2 OUTLETS

EV 2000 130 B DN18

TIN Code	305445
Range	2000
Net weight	416 kg
Insulation	Non-woven polyester 100 mm
Heat losses ΔT 45K	183 W
Energy class	C
Maximum operational temperature	95 °C
Rated pressure of the water tank	8 bar

Diameter	1300 mm

Information

EV 2000 130 B DN18

- **Removable** polyester non-woven **INSULATION f**or models 1500 L - 2000
- High quality **ENAMEL COATING CrystalTech PRO**
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life:
  - **THREE MG+** anodes for models 1500 L and 2000 L
- **SERVICE OPENING** for easy inspection and maintenance.
- Option for **INSTALLATION** of different power rated **HEATING ELEMENTS**.
- Thermoregulator installation pocket.
- Pockets for thermo sensors.

Serie information

EV 2000 130 B DN18

The range includes models from 200 L to 2000 L with energy efficiency class B or C. Suitable for installation in single and multi-family residential buildings as well as for commercial application.

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.