



COMBINED STORAGE TANKS FOR HEATING SYSTEMS AND
DOMESTIC HOT WATER - TANK IN TANK WITHOUT HEAT
EXCHANGERS

V 800 95 EV 200 45 C

TIN Code	303874
Net weight	193 kg
Insulation	100 mm
Heat losses ΔT 45K	128 W
Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	95 °C
Rated pressure of the water tank	10 bar
Rated pressure of the heat exchanger	3 bar
Diameter	990 mm
Number of inlets	4 number
Number of outlets	4 number



Actual capacity buffer tank	608 L
Actual capacity hot water tank	191 L
Minimum height of the premise	2045 mm



Information

V 800 95 EV 200 45 C

- High-quality enamel coating ensuring long operating life
- Low pressure buffer tanks (3 bars), designed to storage and distribute energy from up to 4 different heat sources
- Highly efficient PU insulation
- Efficient anode protection
- Option for installation of an electric heating element
- Option for installation of a thermal regulator
- Option for installation of a thermal sensor

Serie information

V 800 95 EV 200 45 C

Tanks, combining a buffer tank for heating systems and a built-in enameled storage tank for domestic hot water production. The buffer tanks range have volumes from 600 to 1500 liters, and the enameled storage tanks have range with volumes from 150 to 300 liters.