



COMBINED STORAGE TANKS FOR HEATING SYSTEMS AND
DOMESTIC HOT WATER - TANK IN TANK WITH A HEAT
EXCHANGER

V 15 S 600 81 EV 150 40 C

TIN Code	303866
Net weight	188 kg
Insulation	100 mm
Heat exchanger surface S1	2.25 m ²
Heat exchanger capacity S1	13.7 L
Heat losses ΔT 45K	116 W
Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	95 °C
Rated pressure of the heat exchanger	6 bar
Diameter	850 mm
Number of inlets	4 number



Number of outlets	4 number
Maximum working temperature coil heat exchanger	110 °C
Actual capacity buffer tank	416 L
Actual capacity hot water tank	151 L
Minimum height of the premise	2121 mm



Information

V 15 S 600 81 EV 150 40 C

- High-quality enamel coating ensuring long operating life
- Low pressure buffer tanks (3 bars), designed to storage and distribute energy from up to 4 different heat sources
- Highly efficient PU insulation
- Efficient anode protection
- Option for installation of an electric heating element
- Option for installation of a thermal regulator
- Option for installation of a thermal sensor

Serie information

V 15 S 600 81 EV 150 40 C

Tanks, combining a buffer tank for heating systems including a heat exchanger and a built-in enameled storage tank for domestic hot water production. The buffer tanks range have volumes from 600 to 1500 liters, and the enameled storage tanks have range with volumes from 150 to 300 liters.