



COMBINED STORAGE TANKS FOR HEATING SYSTEMS AND  
DOMESTIC HOT WATER - TANK IN TANK WITH A HEAT  
EXCHANGER

V 15S 1000 95 EV 200 45 C

TIN Code	303876
Net weight	274 kg
Insulation	100 mm
Heat exchanger surface S1	3.3 m <sup>2</sup>
Heat exchanger capacity S1	29 L
Heat losses $\Delta T$ 45K	136 W
Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	95 °C
Rated pressure of the heat exchanger	6 bar
Diameter	990 mm
Number of inlets	4 number



Number of outlets	4 number
Maximum working temperature coil heat exchanger	110 °C
Actual capacity buffer tank	666 L
Actual capacity hot water tank	191 L
Minimum height of the premise	2236 mm



## Information

V 15S 1000 95 EV 200 45 C

- High-quality enamel coating ensuring long operating life
- Low pressure buffer tanks (3 bars), designed to storage and distribute energy from up to 4 different heat sources
- Highly efficient PU insulation
- Efficient anode protection
- Option for installation of an electric heating element
- Option for installation of a thermal regulator
- Option for installation of a thermal sensor

## Serie information

V 15S 1000 95 EV 200 45 C

Tanks, combining a buffer tank for heating systems including a heat exchanger and a built-in enameled storage tank for domestic hot water production. The buffer tanks range have volumes from 600 to 1500 liters, and the enameled storage tanks have range with volumes from 150 to 300 liters.