



HEATECO WITH AN ELECTRONIC
THERMOREGULATOR (CN 03)

CN03 200 EIS W



TIN Code	304179
Net weight	5.72 kg
Maximum power	2000 W
Thermo regulator	electronic
For room up to	40-60 m ³
Heating area	16-24 m ²
Height	0.45 m
Width	0.09 m
Length	0.83 m



Information

CN03 200 EIS W

- Maximum power : 2000 W
- Optimal convection - up to 25% faster room heating
- Precise thermoregulator with an accuracy of 0.1°C
- Electronic thermoregulator 10-30°C
- Up to 21% lower electricity costs
- Thermostat calibration to achieve the desired comfort - temperature correction $\pm 4^{\circ}\text{C}$
- Weekly programmer 24h/7d with 30-minute step
- Adaptive start with on/off option - provides optimal comfort and saves energy
- Bathroom installation option - splash proof IP24 protection
- Delayed start function - 96 hours
- Anti-frost protection, fixed on 5°C, with on/off option
- Keyboard lock / children protection
- Overheating protection
- LED display indicating desired and actual room temperature
- Robust metal construction

Serie information

CN03 200 EIS W

HeatEco electric panel convectors achieve 38% of maximum 40% Seasonal Energy Efficiency. This is accomplished thanks to the electronic thermoregulator and ERP related functions ("smart" functions), which save energy and are easy to use. Smart functions include: Open Window/Door Detection; Adaptive Start; Temperature Sensor Correction $\pm 4^{\circ}\text{C}$ and Weekly Programmer 24/7.