



MAXEAU HYBRID

GCV 2005624C D06
S2RCH



TIN Code	305192
Model	MaxEau Hybrid 200
Real Volume	200 L
Height	1.357 m
Width	0.560 m
Depth	0.567 m
Rated power	1200/2400 W
Heating time Δt 45K (15 - 60°C)**80°C	08:42/04:21 h:min
Annual consumption of electricity AEC	2711 kWh



Energy class	C
Diameter	560 mm
Load profile	L
V40	290 L
T _{out of the box}	60 °C
MAX40	354 L



MaxEau Hybrid is a 200 litres electric water heater with extra protection for longer product life. The hybrid technology combines the benefits of a classic magnesium anode and a titanium powered anode.

Upgraded protection against corrosion and lime scale:

Titanium anode:

- Powered by electricity
- As long as the water heater is plugged in, it works as the default
- Not backed up by battery

Magnesium anode:

- Backs up the titanium anode whenever there is no power
- Only activated if titanium anode is not working
- Estimated to last for one year of continuous usage

Suitable for any type of water: The double anode works equally well in soft and hard water

Insulation that keeps water warm for longer:

- 40 mm thickness - highest amongst TESY water heaters
- INSUTECH technology – high density and lack of thermal bridge for extremely low heat losses

Extended life of the water tank thanks to the reliable **CrystalTech enamel coating and plasma welding technology**

Light indication in different colours and intensity notifies the user of the different work regimes in order to improve their experience and optimise the product's operation.

MaxEau Hybrid is a 200 litres electric water heater with extra protection for longer product life. The hybrid technology combines the benefits of a classic magnesium anode and a titanium powered anode.

Upgraded protection against corrosion and lime scale:



Titanium anode:

- Powered by electricity
- As long as the water heater is plugged in, it works as the default
- Not backed up by battery

Magnesium anode:

- Backs up the titanium anode whenever there is no power
- Only activated if titanium anode is not working
- Estimated to last for one year of continuous usage

Suitable for any type of water: The double anode works equally well in soft and hard water

Insulation that keeps water warm for longer:

- 40 mm thickness - highest amongst TESI water heaters
- INSUTECH technology – high density and lack of thermal bridge for extremely low heat losses

Extended life of the water tank thanks to the reliable **CrystalTech enamel coating and plasma welding technology**

Light indication in different colours and intensity notifies the user of the different work regimes in order to improve their experience and optimise the product's operation.