TESY
It's impressive

NON-ENAMELED BUFFER TANKS FOR HEAT PUMP SYSTEMS WITHOUT HEAT EXCHANGERS

V 100 55 ACF W

TIN Code	305432
Range	101
Net weight	30 kg
Insulation	PU 50 mm
Heat losses ΔT 45K	34 W
Energy class	A
Maximum operational temperature	95 °C
Diameter	550 mm
Rated pressure	3 bar

Information

V 100 55 ACF W

- Optimal operation in heating and cooling mode.
- **ANTI-CONDENS SOLUTION**. Additional insulation around all inlets and outlets to prevent condensation in cooling mode.
- High Energy Efficiency Class A.
- 4 inlets and 4 outlets of G1 1/2 size providing high flow rate.
- Additional pockets for air ventilation and draining.
- Inovative stratification nozzles at all inlets and outlets.
- 1 thermosensor pocket.

Serie information

V 100 55 ACF W

Pufer rezervoari, specijalno dizajnirani da budu kompatibilni sa sistemima toplotne pumpe.
Asortiman obuhvata modele od 100 L, 160 L i 200 L, podne, bez izmenjivača toplote.

*Sve prikazane slike služe samo za ilustraciju. Stvarni proizvod može da varira zbog poboljšanja proizvoda.

Težine navedene na ovoj veb stranici su neto vrednosti samo za referentne svrhe. Stvarne težine proizvoda mogu da variraju zbog proizvodnih tolerancija.