



NON-ENAMELED BUFFER TANKS FOR HEAT PUMP SYSTEMS
WITHOUT HEAT EXCHANGERS

V 200 60 ACF W

TIN Code	305434
Range	202
Net weight	47 kg
Insulation	PU 50 mm
Heat losses ΔT 45K	56 W
Energy class	B
Maximum operational temperature	95 °C
Diameter	600 mm
Rated pressure	3 bar



Information

V 200 60 ACF W

- Optimal operation in heating and cooling mode.
- **ANTI-CONDENS SOLUTION.** Additional insulation around all inlets and outlets to prevent condensation in cooling mode.
- High Energy Efficiency Class B.
- 4 inlets and 4 outlets of G1 1/2 size providing high flow rate.
- Additional pockets for air ventilation and draining.
- Innovative stratification nozzles at all inlets and outlets.
- 2 thermosensor pockets.

Serie information

V 200 60 ACF W

Pufer rezervoari, specijalno dizajnirani da budu kompatibilni sa sistemima toplotne pumpe.

Asortiman obuhvata modele od 100 L, 160 L i 200 L, podne, bez izmenjivača toplote.

*Sve prikazane slike služe samo za ilustraciju. Stvarni proizvod može da varira zbog poboljšanja proizvoda.

Težine navedene na ovoj veb stranici su neto vrednosti samo za referentne svrhe. Stvarne težine proizvoda mogu da variraju zbog proizvodnih tolerancija.