



DOMESTIC HOT WATER TANKS WITH TWO DOUBLE HIGH
OUTPUT HEAT EXCHANGERS

EV 2X9 2X17 S2 1000 105
HP DN18 (EPS)

TIN Code	306390 (306824)
Range	921
Net weight	349 kg
Insulation	100 mm
Heat exchanger surface S1	2.50 m ²
Heat exchanger surface S2	4.60 m ²
Heat exchanger capacity S1	14.40 L
Heat exchanger capacity S2	27.50 L
Heat losses ΔT 45K	143 W



Energy class	C
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110 °C
Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar
Diameter	1050 mm



Information

EV 2x9 2x17 S2 1000 105 HP DN18 (EPS)

- **DOUBLE HIGH OUTPUT HEAT EXCHANGER** increases the efficiency of low-temperature heat sources.
- Decreased hydraulic resistance (pressure drop) of the heat exchanger with a larger diameter of the inlet and outlet on G1 1/2. (160 L model with inlets/outlets on G1).
- Heat exchangers with large surfaces for connection to heat pump or condensing gas boiler systems.
- Suitable to operation with low temperature heat sources.
- High quality **ENAMEL COATING** with **TESY CrystalTech PRO** technology.
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life.
- TESI ThermoShell modular removable EPS INSULATION for models 800 L and 1000 L

Serie information

EV 2x9 2x17 S2 1000 105 HP DN18 (EPS)

The range includes models from 200 L to 1000 L. DOUBLE HIGH OUTPUT HEAT EXCHANGER provides optimal operation for low-temperature heat sources.

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.